


Technical Specifications Steinberg AXR4T

MIC/LINE INPUT 1-4 (Balanced)	
Frequency Response	+0.1/-0.1dB, 10Hz to 22kHz @48kHz +0.1/-0.2dB, 10Hz to 44kHz @96kHz +0.1/-0.5dB, 10Hz to 88kHz @192kHz +0.1/-3dB, 10Hz to 100kHz @384kHz
Dynamic Range	119dB, A-Weighted
THD+N	0.0004%, 1kHz, 22Hz/20kHz BPF
Maximum Input Level	+24dBu
Input Impedance	3.3k Ohm
Gain Range	+15dB - +68dB
Pad	-20dB
HI-Z INPUT 1, 2 (Unbalanced)	
Maximum Input Level	+10dBV
Input Impedance	1M Ohm
Gain Range	+15dB - +68dB
Pad	-20dB
LINE INPUT 5-12 (Balanced)	
Frequency Response	+0.1/-0.1dB, 10Hz to 22kHz @48kHz +0.1/-0.2dB, 10Hz to 44kHz @96kHz +0.1/-0.5dB, 10Hz to 88kHz @192kHz +0.1/-3dB, 10Hz to 130kHz @384kHz
Dynamic Range	119dB, A-Weighted
THD+N	0.0006%, 1kHz, 22Hz/20kHz BPF
Maximum Input Level	+24dBu
Input Impedance	20k Ohm
Input Level Select	+4dBu (20dB Headroom), +4dBu (14dB Headroom), -10dBV Selectable
LINE OUTPUT 1-8 (Balanced)	
Frequency Response	+0.1/-0.1dB, 10Hz to 21kHz @48kHz +0.1/-0.3dB, 10Hz to 43kHz @96kHz +0.1/-1dB, 10Hz to 83kHz @192kHz +0.1/-3dB, 10Hz to 120kHz @384kHz
Dynamic Range	117dB, A-Weighted
THD+N	0.0006%, 1kHz, 22Hz/22kHz BPF
Maximum Output Level	+18dBu
Output Impedance	75 Ohm
Digital A I/O Interface	
ADAT	ADAT, Optical, 24-bit
S/PDIF	IEC-60958, Optical, 24-bit
Digital B I/O Interface	
ADAT	ADAT, Optical, 24-bit
S/PDIF	IEC-60958, Optical, 24-bit
AES/EBU	AES/EBU Professional use, RS422, 24-bit

PHONES 1, 2	
Maximum Output Level	75mW+75mW, 40 Ohm
Thunderbolt	
Specification	Thunderbolt 2, 32-bit, 44.1kHz/48kHz/88.2kHz/96kHz/176.4kHz/192kHz/352.8kHz/384kHz
MIDI	
MIDI IN, OUT	DIN 5pin
WORD CLOCK	
WORD CLOCK IN, OUT	TTL/75 ohm
XLR INPUT	
Polarity	1: Ground, 2: Hot (+), 3: Cold (-)

[AES/EBU] Connector



Signal		Data In Ch				Data Out Ch				Open	GND
		1-2	3-4	5-6	7-8	1-2	3-4	5-6	7-8		
		9-10	11-12	13-14	15-16	9-10	11-12	13-14	15-16		
Pin	Hot	1	2	3	4	5	6	7	8	9,11	10,12,13,22,23,24,25
	Cold	14	15	16	17	18	19	20	21		

General Specifications

- Power Requirements 45 W
- Dimensions 480 (W) x 51.5 (H) x 378 (D) mm
- Net weight 4.6kg
- Operating Free-air Temperature Range 0 ~ 40 °C
- Included Accessories
 - AC adaptor (PA-700 or equivalent)
 - Setup Guide (brochure)
 - CUBASE AI DOWNLOAD INFORMATION (printed)
 - ESSENTIAL PRODUCT LICENCE INFORMATION (printed)
 - AXR4 CAUTION SHEET (printed)

System Requirements

Hardware

Product name	AXR4T
OS Version	Mac OS X 10.12 / 10.13
CPU	64-bit Intel multi-core processor (Intel i5 or faster recommended)
Memory	4 GB or more
HDD	Free disk space of 1.5GB or more; high-speed hard disk
Display Resolution	1440 x 900—full color
Interface	Equipped with a Thunderbolt2 connector
Others	Internet connection required for download, installation, activation, account setup and personal / product registration.

Bundled Software (DOWNLOAD)

Product name	TOOLS for AXR4T
OS Version	Mac OS X 10.12 / 10.13
CPU	64-bit Intel multi-core processor (Intel i5 or faster recommended)
Memory	4 GB or more
HDD	Free disk space of 1.5GB or more; high-speed hard disk
Display Resolution	1440 x 900—full color
Interface	Equipped with a Thunderbolt2 connector
Others	When using the link function between the device and Cubase - Cubase 9.5 series or later Internet connection required for download, installation, activation, account setup and personal / product registration.

Bundled Software (DOWNLOAD)

Product name	CUBASE AI 10
OS Version	Mac OS X 10.11 / 10.12 / 10.13
CPU	64-bit Intel multi-core processor (Intel i5 or faster recommended)
Memory	4 GB RAM (8 GB or more recommended)
HDD	12 GB free HD space
Display Resolution	1366 x 768 display resolution (1920 x 1080 recommended)
Others	Internet connection required for activation, account setup, access to manual and personal/product registration. Additional downloads may be required for the installation.

